

IN THE CLAIMS

What we claim is:

- 1 1. (currently amended) A multilayered circuit component comprising:
2 two or more layers;
3 a first surface of the two or more layers upon which a first plurality of circuit
4 paths are provided;
5 a second surface of the two or more layers upon which a second plurality of
6 circuit paths are provided;
7 an aperture extending through at least a portion of the two or more layers, the
8 aperture being defined by a first opening on the first surface, a second opening on the
9 second surface, and ~~an internal surface~~ surfaces of the two or more layers that extend
10 extends between the first surface and the second surface;
11 a first trace element provided over a portion of one of the internal surfaces
12 of the aperture to extend between the first surface and the second surface, the first trace
13 element extending onto the first surface to form a first partial perimeter of the first
14 opening;
15 wherein the first trace element is formed by plating a first hole through ~~on~~ the first
16 surface, and then subsequently forming the aperture to intersect the first hole, so that after
17 the aperture is formed, a remaining portion of the first hole has plating that forms the first
18 trace element;
19 a second trace element provided over a portion of one of the internal surfaces of
20 the aperture to extend between the first surface and the second surface, the second trace
21 element extending onto the first surface to form a second partial perimeter of the first
22 opening; and
23 wherein the first trace element and the second trace element are formed by plating
24 the first hole and a second hole on the first surface, and then subsequently forming the
25 aperture to intersect the first hole and the second hole, so that after the aperture is formed,
26 the remaining portion of the first hole has plating that forms the first trace element, and a
27 remaining portion of the second hole has plating that forms the second trace element, and

28 wherein the first trace element and the second trace element each form a pedal shaped
29 support element on the first surface.

1 Claims 2 and 3 canceled.

1 4. (currently amended) The component of claim 1, wherein at least one of the
2 internal surfaces ~~first surface or the second surface~~ is a grounding plane.

1 5. (currently amended) The component of claim 1, wherein at least one of the
2 internal surfaces ~~first surface or the second surface~~ is a power plane.

1 6. (currently amended) The component of claim 1 ~~claim 2~~, wherein each of the first
2 trace element and the second trace element is rounded as it extends on one of the internal
3 surfaces ~~surface~~ of the aperture.

1 7. (currently amended) The component of claim 1 ~~claim 2~~, wherein the aperture has
2 an irregular cross-section, and wherein each of the first trace element and the second
3 trace element is rounded as it extends on one of the internal surface of the aperture.

1 8. (currently amended) The component of claim 1 ~~claim 2~~, wherein the component
2 forms part of a backplane.

1 9. (currently amended) The component of claim 1 ~~claim 2~~, wherein the first trace
2 element has a radius of curvature that defines a corresponding circle, and wherein the
3 first trace element has an arc length that is less than 50% of a circumference of the
4 corresponding circle.

1 10. (currently amended) The component of claim 1 ~~claim 2~~, wherein the arc length of
2 the first trace element is less than 33% of the circumference of the corresponding circle.

1 11. (currently amended) ~~The component of claim 2,~~ A multilayered circuit component
2 comprising:

3 two or more layers;

4 a first surface of the two or more layers upon which a first plurality of circuit
5 paths are provided;

6 a second surface of the two or more layers upon which a second plurality of
7 circuit paths are provided;

8 an aperture extending through at least a portion of the two or more layers, the
9 aperture being defined by a first opening on the first surface extending through to the
10 second surface, a second opening on the second surface, and internal surfaces of the two
11 or more layers that extends between the first surface and the second surface;

12 a first trace element provided over a portion of one of the internal surfaces of the
13 aperture to extend between the first surface and the second surface, the first trace element
14 extending onto the first surface to form a first partial perimeter of the first opening;

15 wherein the first trace element is formed by plating a first hole on the first surface,
16 and then subsequently forming the aperture to intersect the first hole, so that after the
17 aperture is formed, a remaining portion of the first hole has plating that forms the first
18 trace element, and wherein the first trace element has a radius of curvature that defines a
19 first circle, the second trace element has a radius of curvature that defines a second circle,
20 and wherein the first trace element and the second trace element each have an arc length
21 that is less than 50% of a circumference of the corresponding first or second circle;

22 a second trace element provided over a portion of the one of internal surfaces of
23 the aperture to extend between the first surface and the second surface, the second trace
24 element extending onto the first surface to form a second partial perimeter of the first
25 opening; and

26 wherein the first trace element and the second trace element are formed by plating
27 the first hole and a second hole on the first surface extending through to the second
28 surface, and then subsequently forming the aperture to intersect the first hole and the
29 second hole, so that after the aperture is formed, the remaining portion of the first hole
30 has plating that forms the first trace element, and a remaining portion of the second hole
31 has plating that forms the second trace element.

1 12. (original) The component of claim 1, wherein the aperture has an irregular cross-
2 sectional shape.

1 13. (original) The component of claim 1, wherein a cross-section of the aperture is
2 shaped to have a plurality of different radii of curvatures.

1 14. (currently amended) A multilayered circuit component comprising:
2 two or more layers;
3 a first surface of a first layer in the two or more layers, the first surface containing
4 one or more circuit elements;
5 an array of apertures extending through at least a portion of the first layer to
6 extend between the first surface and at least one other surface of the two or more layers,
7 each aperture in the array having a first opening on the first surface;
8 one or more discrete trace elements provided over an interior surface of each
9 aperture in the array, each trace element extending between the first surface and the at
10 least one other surface of the two or more layers, and each trace element forming a
11 portion of a cross-sectional perimeter of the aperture which contains that trace element;
12 wherein each aperture is shaped to receive a corresponding male connector
13 element that can extend into the aperture and make electrical contact with the one or
14 more trace elements that are provided in that aperture, so that another layer comprising an
15 array of male connectors is matable with the component using the array of apertures of
16 the first surface.

1 15. (original) The component of claim 14, wherein one or more of the apertures in
2 the array contain one or more trace elements that extend from the respective apertures
3 and form a corresponding pedal shaped support element on the first surface.

1 16. (original) The component of claim 14, wherein one or more of the apertures in
2 the array contain one or more trace elements that are rounded as they extend into the
3 respective aperture.

1 17. (currently amended) A multilayered circuit component comprising:
2 two or more layers;

3 a first surface of the two or more layers upon which a first plurality of circuit
4 paths are provided;
5 a second surface of the two or more layers upon which a second plurality of
6 circuit paths are provided;
7 an aperture extending through at least a portion of the two or more layers, the
8 aperture being defined by a first opening on the first surface, a second opening on the
9 second surface, and an internal ~~surfaces surface~~ of the two or more layers that extends
10 between the first surface and the second surface;
11 a first trace element provided over a first portion of one of the internal surfaces
12 ~~surface~~ of the aperture to extend between the first surface and the second surface, the first
13 trace element being rounded and extending onto the first surface to form a first partial
14 perimeter of the first opening, wherein the first partial perimeter of the first opening has a
15 first radius of curvature, the second partial perimeter of the first opening has a second
16 radius of curvature, and another perimeter portion of the opening has a third radius of
17 curvature, wherein at least the third radius of curvature is different than the first radius of
18 curvature and the second radius of curvature;
19 a second trace element provided over a second portion of one of the internal
20 surfaces surface of the aperture to extend between the first surface and the second
21 surface, the second trace element being rounded and extending onto the second surface to
22 form a second partial perimeter of the first opening;
23 wherein the opening of the aperture has a plurality of radii of curvatures.

1 Claim 18 canceled.

1 19. (original) A multilayered circuit component comprising:
2 an array of input/output contact points provided on a first surface of the first layer
3 of the circuit component;
4 a plurality of trace element clusters, each trace element cluster extending inward
5 from the first surface of the first layer to an other surface of the multi-surfaced circuit
6 component, wherein each trace element cluster includes at least (i) a first trace element
7 for providing a first connection to one or more current bearing components on the other
8 surface that the first trace element extends to, and (ii) a second trace element for

9 providing a second connection to one or more current bearing components on the other
10 surface that the second trace element extends to; and
11 wherein at least some of the trace element clusters are positioned interstitially
12 between two or more input/output contact points in the array.

1 20. (original) The component of claim 19, wherein at least some of the trace element
2 clusters are positioned interstitially between a set of four input/output contact points in
3 the array.

1 21. (original) The component of claim 19, wherein at least one trace element cluster
2 provides that the first trace element contacts a ground or power plane.

1 22. (original) The component of claim 19, wherein at least some of the trace element
2 clusters include four or more trace elements, wherein each of the four or more trace
3 elements makes a distinct connection with a current bearing component on another
4 surface.

1 23. (original) The component of claim 19, wherein the interstitially positioned trace
2 element clusters are disposed within the array so that one or more channels for extending
3 escape lines are formed.